



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

A FILTRATION SYSTEM FOR MAGNESIUM RECYCLING AND PURIFICATION

Field Of Invention

- 5 The present invention relates generally to a filtration system for purifying magnesium. Specifically, the present invention relates to a filtration system for recycling and purification of scrap magnesium and magnesium ingots with impurities.

Background

- 10 Magnesium alloys are heated to a molten state in preparation for hot-working thereof. Molten magnesium alloys easily oxidise and react with impurities, especially when scrap magnesium alloys are reused. As a result, magnesium alloys are contaminated by non-metallic and metallic inclusions, for example oxides or intermetallic compounds, when melted.

15

The magnesium alloys are typically melted for producing castings. The presence of inclusions within the magnesium alloys results in metallurgical defects therein and will adversely affect the quality of the castings produced from the magnesium alloys.

- 20 A known method for removing the impurities is to send the magnesium alloys to a smelter for smelting. However, smelting is a costly process. Another known process uses impediment plates disposed within a furnace for removing top and bottom sludge from magnesium melts. However, the impediment plates do not remove inclusions suspended in the magnesium melts.

25

Hence, this clearly affirms a need for a filtration system for purifying magnesium melts.

Summary

In accordance with a first aspect of the invention, there is disclosed a filtration system for magnesium recycling and purification, the filtration system comprising:

5 a first chamber for containing magnesium melt, the magnesium melt containing impurities; and

 a second chamber for receiving purified magnesium melt,

 wherein said first and second chambers have disposed therebetween a filter, the filter being a silicon-free medium.

10

In accordance with a second aspect of the invention, there is disclosed a filtration method for magnesium recycling and purification, comprising the steps of:

 receiving magnesium melt into a first chamber, the magnesium melt containing impurities within the first chamber containing impurities;

15 providing a second chamber, the second chamber being in fluid communication with the first chamber; and

 substantially removing the impurities from the magnesium melt flowing from the first chamber into the second chamber using a filter, the filter being disposed between the first chamber and the second chamber and the filter including a silicon-free medium.

20

In accordance to a third aspect of the invention, there is disclosed a filtration method for magnesium recycling and purification, comprising the steps of:

25 receiving magnesium into a first chamber, the magnesium within the first chamber containing impurities and the magnesium being one of a magnesium melt or solid magnesium ingot;

 providing a second chamber, the second chamber being in fluid communication with the first chamber;

30 heating the magnesium contained in the first chamber by a heating apparatus for melting the magnesium and for maintaining the magnesium melt in a molten state, and the magnesium melt in the first chamber thereby flowing into the second chamber; and

substantially removing the impurities from the magnesium melt flowing from the first chamber into the second chamber using a filter, the filter being disposed between the first chamber and the second chamber and the filter including a silicon-free medium.

5

Brief Description Of The Drawings

Embodiments of the invention are described hereinafter with reference to the following drawings, in which:

10 FIG. 1 shows a partial front sectional view of a filtration system according to an embodiment of the invention;

FIG. 2 shows a partial side sectional view of the filtration system of FIG. 1;

15 FIG. 3 is an illustration of a filter of the filtration system of FIG. 1;

FIG. 4 is an illustration of a first chamber and the filter of FIG. 3;

20 FIG. 5a shows a low magnification light optical microscope (LOM) micrograph of a tensile specimen made from magnesium melt obtained from the filtration system of FIG. 1;

FIG. 5b shows the LOM micrograph of FIG. 5a under high magnification;

25 FIG. 6a shows a low magnification light optical microscope (LOM) micrograph of a mobile phone case specimen made from magnesium melt obtained from the filtration system of FIG. 1;

FIG. 6b shows the LOM micrograph of FIG. 6b under high magnification;

30

FIG. 7a shows a graph plotting the tensile strength (ultimate tensile strength and yield strength) of test samples as a function of cross-head speed with the test samples being cast from a magnesium melt purified using the filtration system of FIG. 1; and

FIG. 7b shows a graph plotting the percentage elongation of the test samples of FIG. 7b, as a function of cross-head speed.

5 Detailed Description

An embodiment of the invention, a filtration system 20 is described with reference to FIG. 1, which shows a partial front sectional view of the filtration system 20 and FIG. 2 which shows a partial side sectional view of the filtration system 20. The filtration system 20 is for use in substantially purifying magnesium.

10

As shown in FIG. 1, the filtration system 20 includes a crucible 22 being divided into two parts by a filter adapter 24 disposed therein, the two parts of the crucible being namely a first chamber 26 and a second chamber 28. The first chamber 26 is in fluid communication with the second chamber 28 through an opening 30, as shown in FIG.

15

2, in the filter adapter 24 that forms a passageway therebetween.

20

As shown in FIG. 2, the filter adapter 24 is for receiving a filter 32 therewithin and for removably engaging thereto. FIG. 3 is an illustration of the filter 32 and FIG. 4 is an illustration of the first chamber 26 and the filter 32. When the filter 32 is engaged to the filter adapter 24, the filter 32 blocks the opening 30 of the filter adapter 24, thereby intersecting the passageway between the first chamber 26 and the second chamber 28, as shown in FIGS. 1, 2 and 5. The filter adapter 24 is preferably a steel structure that shaped and dimensioned for holding the filter 32 at the periphery thereof.

25

The filtration system 20 further includes a heating apparatus coupled to the crucible 22. The heating apparatus is preferably integrated with the crucible 22 for providing heat to the crucible 22 and its contents. The heating apparatus is electrically connected to a controller (all not shown).

30

The filtration system 20 is for providing substantially purified magnesium melts to downstream systems or machineries, for example, a die-casting machine. For obtaining purified magnesium melts from the filtration system 20, magnesium ingots

or scraps are provided to the first chamber 26 of the filtration system 20. The controller activates the heating apparatus to provide heat to the crucible 22 and the magnesium therein, thereby melting the magnesium.

- 5 Alternatively, magnesium melt can be provided to the first chamber 26 of the crucible 22. The heating apparatus provides heat to the crucible 22 to maintain the magnesium melt in its molten state and to melt the magnesium scraps and ingots added to the magnesium melt thereafter.
- 10 The filter 32 of the filtration system 20 is preferably made of a silicon-free material. Conventional filters, for example a filter for aluminium alloys, are made of silicon-based materials. The silicon-based materials readily react with magnesium to cause contamination therein and are therefore undesirable. The filter 32 is made of one of steels or ceramic material which comprises of one or more material selected from a
- 15 group consisting of Al_2O_3 , MgO , AlPO_4 and $\text{Mg}_3(\text{PO}_4)_2$.

The filter 32 comprises of an array of apertures (not shown). Each of the apertures is shaped and dimensioned for preventing the passage of a particle having a size greater than 5 microns therethrough. Preferably, each pair of adjacent apertures are spaced

20 apart a distance of 5 to 250 microns. The magnesium melt 38 in the first chamber 26 passes through the filter 32 and into the second chamber 28 of the crucible 22. Therefore, the impurities suspended in the magnesium melt 38 contained in the first chamber 26 is substantially removed by the filter 32 before entering the second chamber 28 as purified magnesium melt 40. The magnesium melt 38 contained in the

25 first chamber 26 contains bottom sludge that has settled at the bottom of the first chamber 26. In most situations, top sludge can also be found floating at the surface of the magnesium melt 38 contained in the first chamber 26. The filter adapter 24 functions to substantially impede the top sludge and bottom sludge in the first chamber 26 from entering the second chamber 28 (all not shown).

30

With reference to FIG. 1, the magnesium melt 38 in the first chamber 26 is drawn into the second chamber 28 by hydrostatic forces acting on the magnesium melt 38. The magnesium melt 38 in the first chamber 26 continues to be drawn into the second

chamber until the hydrostatic pressures of magnesium melt 38 in the first chamber 26 and the purified magnesium melt 40 in the second chamber 28 are in equilibrium.

Preferably, each of the first chamber 26 and the second chamber 28 has a thermocouple 42 disposed therewithin. Both the thermocouples 42 are electrically connected to the controller for transducing temperature of the magnesium melt 38 in the first chamber 26 into first temperature signals (not shown) and the temperature of the purified magnesium melt 40 in the second chamber 40 into second temperature signals (not shown). The first and second temperature signals are transmitted to the controller. From the first and second temperature signals, the controller uses a control function (not shown) to determine and control the heat output of the heating apparatus, thereby maintaining the magnesium melt 38 and the purified magnesium melt 40 in a molten state and to prevent overheating thereof. In the molten state, the viscosities of both the magnesium melt 38 and the purified magnesium melt 40 are greatly reduced, thereby facilitating flow thereof through the filter 32.

The crucible 22 is preferably enclosed for receiving and retaining protective gas therein. A gas feed system (not shown) is connected to the crucible for supplying the protective gas thereinto. The protective gas prevents both the magnesium melt 38 and the purified magnesium melt 40 from reacting with the atmosphere by forming a screen therebetween.

An extractor 44, as shown in FIG. 1, extends from within the second chamber 28 to a die-casting assembly 46. The extractor 44 is for extracting the purified magnesium melt 40 from the second chamber 28 and providing the purified magnesium melt 40 to the die-casting assembly 46. The extractor 44 shown in FIG. 1 uses a piston and a goose-neck chamber assembly for extracting the purified magnesium melt 40.

Extracting the purified magnesium melt 40 from the second chamber 28 reduces the level of the purified magnesium melt 40 contained therein. The reduction of the level of the purified magnesium melt 40 in the second chamber 28 further draws the magnesium melt 38 from the first chamber 26 and into the second chamber 28. Magnesium melt and magnesium ingots or scraps can be further provided to the first

chamber 26 for replenishing the second chamber 28 and thereby the filtration system 20 with purified magnesium melt 40.

5 The purified magnesium melt 40 supplied from the filtration system 20 to the die-casting assembly 46 provides the die-casting assembly with a substantially inclusion-free purified magnesium melt 40 supply for use in a die-casting process.

10 Two types of parts, hand-phone case and tensile test specimens, were cast during tests. The alloy used in the tests was AZ91 HP having a composition of Al 8-9.5%, Zn 0.3-1.0%, Mn $\geq 0.17\%$, Si $\leq 0.05\%$, Fe $\leq 0.004\%$, Cu $\leq 0.015\%$, Ni $\leq 0.01\%$, others $\leq 0.01\%$, others $\leq 0.01\%$, Mg (remaining). For comparison the tests were conducted using 100% fresh ingot and ingot including 10% scraps material.

15 After casting, the microstructure and chemical properties of the specimens were analyzed. The microstructure analysis was conducted with light optical microscopy (LOM) while mechanical properties were determined using an Instron tensile testing machine. The cross-head speed was varied from 0.1 to 20 mm/min during tensile tests.

20 Typical microstructures for the tensile test specimen, having a diameter of 10 mm-thick walled part and a mobile phone case, having a wall thickness of 0.6mm-thin wall part. In both thick and thin walled parts, the microstructures consist mainly of α -Mg, intermetallic- $\text{Al}_2\text{Mg}_{17}$, eutectic composition and some fine precipitate. However, the thin walled parts showed much finer structure, as shown in FIGS. 7a and 7b, when compared to the thick walled parts shown in FIGS. 6a and 6b. The
25 reduced α -Mg grain size is due to rapid solidification rate occurred in the thin walled part.

30 Mechanical properties of cast samples were determined after casting. FIGS. 8a and 8b show the tensile strength, comprising the ultimate tensile strength (UTS) and yield strength (YS) and elongation as a function of the cross-head speed. As the cross-head speed is directly related to the strain rate of the testing, the results obtained indicated

that the strain rate has a very slight influence on the flow stress and strain of magnesium castings when tested at room temperature. The UTS and YS are about 142 and 119 MPa respectively with an elongation of about 1%.

- 5 A comparison was made between the mechanical properties of castings made with filtered magnesium (with about 10% scraps) and castings made with fresh magnesium (100% new ingot). The strength of the castings is increased when filtered magnesium is used as compared to when 100% new magnesium ingot is used. However, the ductility of the magnesium alloys is reduced. The decreased ductility is typically due
10 to the presence of more intermetallic compounds and less magnesium in the alloy having scrap parts therein although the alloy has already been filtered. Therefore, the composition of the alloy should be adjusted when using scrap parts.

- In the foregoing manner, a filtration system is described according to an embodiment
15 of the invention for addressing the foregoing disadvantages of conventional filtration devices. Although only one embodiment of the invention is disclosed, it will be apparent to one skilled in the art in view of this disclosure that numerous changes and/or modification can be made without departing from the scope and spirit of the invention.

Claims

1. A filtration system for magnesium recycling and purification, the filtration system comprising:
 - a first chamber for containing magnesium melt, the magnesium melt containing impurities; and
 - a second chamber for receiving purified magnesium melt, wherein said first and second chambers have disposed therebetween a filter, the filter being a silicon-free medium.
2. The filtration system as in claim 1, the second chamber being in fluid communication with the first chamber and the filter for substantially removing the impurities from the magnesium melt flowing from the first chamber into the second chamber.
3. The filtration system as in claim 1, further comprising:
 - a heating apparatus integrated with the first and second chambers for maintaining the magnesium melt contained in the first and second chambers in a molten state.
4. The filtration system as in claim 1, further comprising:
 - a filter adapter disposed between the first chamber and the second chamber, the filter being removably coupled to the filter adapter and the filter adapter for positioning the filter to interface the first chamber and the second chamber.
5. The filtration system as in claim 1, the filter comprising one of steel or ceramic material.
6. The filtration system as in claim 5, the filter further comprises at least one material selected from a group consisting of Al_2O_3 , MgO , AlPO_4 and $\text{Mg}_3(\text{PO}_4)_2$.

10

7. The filtration system as in claim 1, the filter comprising an array of at least one aperture.
- 5 8. The filtration system as in claim 7, each of the at least one aperture being shaped and dimension for preventing passage of a particle having a size greater than 5 microns therethrough.
9. The filtration system as in claim 7, each pair adjacent apertures being spaced apart a distance of 5 to 250 microns.
- 10 10. The filtration system as in claim 1, further comprising a temperature control system for regulating temperature of the magnesium melt within the first chamber and the second chamber.
- 15 11. The filtration method as in claim 10, the temperature control system comprising:
a controller, the heating apparatus being electrically connected to the controller;
a first thermocouple being electrically connected to the controller and
20 being disposed within the first chamber for transducing temperature of the magnesium melt therein into first temperature signals; and
a second thermocouple being electrically connected to the controller and being disposed within the second chamber for transducing temperature of the filtered magnesium melt therein into second temperature signals,
25 wherein the first temperature signals and the second temperature signals are transmitted to the controller, the controller having a control function for controlling the heating apparatus and thereby maintaining the magnesium melt in a molten state and preventing overheating of the magnesium melt.
- 30 12. The filtration system as in claim 1, further comprising a gas feed system for introducing a protective gas in to the first and second chambers.

13. The filtration method as in claim 1, further comprising a step of:
an extractor for extracting the magnesium melt from the second chamber, the extractor being extending from within the second chamber to a die-casting assembly, the extractor for providing the extracted magnesium melt to the die-casting assembly.
14. A filtration method for magnesium recycling and purification, comprising the steps of:
receiving magnesium melt into a first chamber, the magnesium melt containing impurities within the first chamber containing impurities;
providing a second chamber, the second chamber being in fluid communication with the first chamber; and
substantially removing the impurities from the magnesium melt flowing from the first chamber into the second chamber using a filter, the filter being disposed between the first chamber and the second chamber and the filter including a silicon-free medium.
15. The filtration system as in claim 14, further comprising a step of:
providing a heating apparatus integrated with the first and second chambers for maintaining the magnesium melt contained in the first and second chambers in a molten state.
16. The filtration method as in claim 14, the filter comprising a silicon-free material.
17. The filtration method as in claim 15, further comprising a step of:
providing a temperature control system for regulating temperature of the magnesium melt within the first chamber and the second chamber.
18. The filtration method as in claim 17, the temperature control system comprising:
a controller, the heating apparatus being electrically connected to the controller;

a first thermocouple being electrically connected to the controller and being disposed within the first chamber for transducing temperature of the magnesium melt therein into first temperature signals; and

a second thermocouple being electrically connected to the controller and being disposed within the second chamber for transducing temperature of the filtered magnesium melt therein into second temperature signals,

wherein the first temperature signals and the second temperature signals are transmitted to the controller, the controller having a control function for controlling the heating apparatus and thereby maintaining the magnesium melt in a molten state and preventing overheating of the magnesium melt.

19. The filtration method as in claim 14, further comprising a step of:

extracting the magnesium melt from the second chamber by an extractor, the extractor extending from within the second chamber to a die-casting assembly, the extractor for providing the extracted magnesium melt to the die-casting assembly.

20. A filtration method for magnesium recycling and purification, comprising the steps of:

receiving magnesium into a first chamber, the magnesium within the first chamber containing impurities and the magnesium being one of a magnesium melt or solid magnesium ingot;

providing a second chamber, the second chamber being in fluid communication with the first chamber;

heating the magnesium contained in the first chamber by a heating apparatus for melting the magnesium and for maintaining the magnesium melt in a molten state, and the magnesium melt in the first chamber thereby flowing into the second chamber; and

substantially removing the impurities from the magnesium melt flowing from the first chamber into the second chamber using a filter, the filter being disposed between the first chamber and the second chamber and the filter including a silicon-free medium.




Fig. 1




Fig. 2

3/8




Fig. 3

4/8




Fig. 4

5/8




Fig. 5b




Fig. 5a

6/8




Fig. 6b




Fig. 6a




Fig. 7a




Fig. 7b

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SG 02/00238

CLASSIFICATION OF SUBJECT MATTER

IPC⁷: C22B 9/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC⁷: C22B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4092153 A (YARWOOD et al.) 30 May 1978 (30.05.78) <i>column 2, line 66 - column 3, line 25; column 4, lines 17-31; column 6, lines 6-35; claims 1,2.</i>	1,2,4,5,7,14
X	US 4081371 A (YARWOOD et al.) 28 March 1978 (28.03.78) <i>abstract; column 2, lines 36-54; claims 1,4.</i>	1,2,4,5,7,14
X	US 4640497 A (HEAMON) 3 February 1987 (03.02.87) <i>column 1, lines 31-64; column 2, lines 27-53; claims 1,3-5; figures 1-3.</i>	1,4,5,7,14
Y		3,10,15,17, 18, 20
X	US 4124506 A (DORE) 7 November 1978 (07.11.78) <i>abstract; column 3, lines 16-26; claims 1,2,4,9.</i>	1,2,7,14
Y		3,10,15,17, 18,20

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

„A“ document defining the general state of the art which is not considered to be of particular relevance

„E“ earlier application or patent but published on or after the international filing date

„L“ document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

„O“ document referring to an oral disclosure, use, exhibition or other means

„P“ document published prior to the international filing date but later than the priority date claimed

„T“ later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

„X“ document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

„Y“ document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

„&“ document member of the same patent family

Date of the actual completion of the international search

9 December 2002 (09.12.2002)

Date of mailing of the international search report

20 December 2002 (20.12.2002)

Name and mailing address of the ISA/AT

Austrian Patent Office

Kohlmarkt 8-10; A-1014 Vienna

Facsimile No. 1/53424/535

Authorized officer

KOLLER G.

Telephone No. 1/53424/458

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SG 02/00238

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 95/12000 A1 (ALUMINIUM PECHINEY) 4 May 1995 (04.05.95) <i>abstract; page 4, lines 27-30; claims 2,4,9.</i>	3,10,15,17, 18,20
Y	US 3843355 A (REDING) 22 October 1974 (22.10.74) <i>column 2, lines 46-68; claims 1-16.</i>	3,10,15,17, 18,20
X	JP 04 026725 A (NGK INSULATORS LTD) 29 January 1992 (29.01.92) (abstract). [online] [retrieved on 21.11.2002]. Retrieved from: EPOQUE PAJ Database	6

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/SG 02/00238-0

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
JP	A	26725A2		none	
US	A	3843355	22-10-1974	BR A0 7302410	12-11-1974
				CA A1 980579	30-12-1975
				DE A1 2316385	18-10-1973
				FR A1 2179058	16-11-1973
				FR B1 2179058	26-12-1975
				GB A 1424543	11-02-1976
				IT A 980090	30-09-1974
				JP A2 49009411	28-01-1974
				JP B4 56018063	25-04-1981
				NL A 7304616	08-10-1973
				NO B 133148	08-12-1975
				NO C 133148	17-07-1979
US	A	4081371	28-03-1978	AT A 2253/76	15-05-1981
				AT B 365088	10-12-1981
				BR A 7601848	28-09-1976
				CA A1 1059535	31-07-1979
				CH A 622230	31-03-1981
				DE A1 2613023	07-10-1976
				DE U1 7609437	19-11-1981
				DE C2 2613023	18-11-1982
				DE C2 2660717	19-04-1990
				FR A1 2305407	22-10-1976
				FR B1 2305407	21-01-1983
				GB A 1537548	29-12-1978
				GB A 1537549	29-12-1978
				IT A 1060714	20-08-1982
				JP A2 60005828	12-01-1985
				JP B4 60017563	04-05-1985
				JP B4 2022129	17-05-1990
				NL B 182289	16-09-1987
				NL C 182289	16-10-1992
				NO A 761038	29-09-1976
				NO A 801371	29-09-1976
				NO B 148381	20-06-1983
				NO C 148381	28-09-1983
				NO B 150165	21-05-1984
				NO C 150165	29-08-1984
				US A 4024056	17-05-1977
				YU A 782/76	27-04-1983
				YU B 37100	31-08-1984
				US A 4032124	28-06-1977
				US A 4052198	04-10-1977
				US A 4092153	30-05-1978
				US A 4154689	15-05-1979
				US A 4024212	17-05-1977
				JP A2 51142162	07-12-1976
				NL A 7603208	30-09-1976
				US A 4075303	21-02-1978
				US A 3962081	08-06-1976
				US A 3947363	30-03-1976
				BE A1 840066	16-07-1976
				ZA A 7601824	30-03-1977
				AT A 656/77	15-05-1980
				AT B 360236	29-12-1980
				BE A1 850998	31-05-1977
				BR A 7700588	18-10-1977
				CA A1 1090587	02-12-1980
				CH A 626653	30-11-1981
				DE A1 2704301	11-08-1977
				FR A1 2339676	26-08-1977
				GB A 1569779	18-06-1980
				IT A 1067961	21-03-1985
				JP A2 52113304	22-09-1977
				JP B4 54037081	13-11-1979
				NL A 7701085	04-08-1977
				NO A 770320	03-08-1977
				ZA A 7700480	28-12-1977
				US A 3893917	08-07-1975
				US A 4056586	01-11-1977
US	A	4092153	30-05-1978	AT A 2253/76	15-05-1981
				AT B 365088	10-12-1981
				BR A 7601848	28-09-1976
				CA A1 1059535	31-07-1979
				CH A 622230	31-03-1981

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/SG 02/00238-0

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
				DE A1 2613023	07-10-1976
				DE U1 7609437	19-11-1981
				DE C2 2613023	18-11-1982
				DE C2 2660717	19-04-1990
				FR A1 2305407	22-10-1976
				FR B1 2305407	21-01-1983
				GB A 1537548	29-12-1978
				GB A 1537549	29-12-1978
				IT A 1060714	20-08-1982
				JP A2 60005828	12-01-1985
				JP B4 60017563	04-05-1985
				JP B4 2022129	17-05-1990
				NL B 182289	16-09-1987
				NL C 182289	16-10-1992
				NO A 761038	29-09-1976
				NO A 801371	29-09-1976
				NO B 148381	20-06-1983
				NO C 148381	28-09-1983
				NO B 150165	21-05-1984
				NO C 150165	29-08-1984
				US A 4024056	17-05-1977
				YU A 782/76	27-04-1983
				YU B 37100	31-08-1984
				US A 4032124	28-06-1977
				US A 4052198	04-10-1977
				US A 4081371	28-03-1978
				US A 4154689	15-05-1979
				AT A 656/77	15-05-1980
				AT B 360236	29-12-1980
				BE A1 850998	31-05-1977
				BR A 7700588	18-10-1977
				CA A1 1090587	02-12-1980
				CH A 626653	30-11-1981
				DE A1 2704301	11-08-1977
				FR A1 2339676	26-08-1977
				GB A 1569779	18-06-1980
				IT A 1067961	21-03-1985
				JP A2 52113304	22-09-1977
				JP B4 54037081	13-11-1979
				NL A 7701085	04-08-1977
				NO A 770320	03-08-1977
				ZA A 7700480	28-12-1977
				US A 4024212	17-05-1977
				JP A2 51142162	07-12-1976
				NL A 7603208	30-09-1976
				US A 4075303	21-02-1978
				US A 3962081	08-06-1976
				US A 3947363	30-03-1976
				BE A1 840066	16-07-1976
				ZA A 7601824	30-03-1977
				US A 3893917	08-07-1975
				US A 4056586	01-11-1977
US	A	4124506	07-11-1978	none	
US	A	4640497	03-02-1987	AT E 50918	15-03-1990
				AU A1 64089/86	19-05-1987
				AU B2 598759	05-07-1990
				BR A 8606944	03-11-1987
				CA A1 1287974	27-08-1991
				CN A 86107248	29-04-1987
				CN B 1006681	07-02-1990
				DD A5 252204	09-12-1987
				DE C0 3669442	19-04-1990
				DK A 3184/87	23-06-1987
				DK A0 3184/87	23-06-1987
				EP A1 243384	04-11-1987
				EP B1 243384	14-03-1990
				ES AF 2003411	01-11-1988
				JP T2 63502359	08-09-1988
				JP B4 3061731	20-09-1991
				MX B 166669	27-01-1993
				NO A 872618	23-06-1987
				NO A0 872618	23-06-1987
				NZ A 217952	27-01-1989
				SU A3 1595344	23-09-1990
				WO A1 8702596	07-05-1987

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/SG 02/00238-0

Patent document cited in search report				Publication date		Patent family member(s)		Publication date
WO	A1	9512000	04-05-1995	ZA	A	8607882		24-06-1987
				AT	E	155823		15-08-1997
				AU	A1	80640/94		22-05-1995
				AU	B2	676621		13-03-1997
				CA	AA	2175073		04-05-1995
				DE	C0	69404477		28-08-1997
				DE	T2	69404477		05-02-1998
				EP	A1	725840		14-08-1996
				EP	B1	725840		23-07-1997
				ES	T3	2104431		01-10-1997
				FR	A1	2711560		05-05-1995
				FR	B1	2711560		24-11-1995
				GR	T3	3024251		31-10-1997
				JP	T2	9504339		28-04-1997
				NO	A	961602		22-04-1996
				NO	A0	961602		22-04-1996
				NO	B1	309577		19-02-2001
				SI	T1	725840		31-08-1998